ES5200 SERIES ENTRY SENTRY - USER INSTRUCTIONS



-copy and distribute this page to users-

OVERVIEW

The Entry Sentry establishes a threshold allowing only one passage per validated user.

The Detection Area senses the presence and direction of travel of each user.

Any intrusion into the Detection Area by an non-validated user will generate an alarm.

The Entry Sentry can accept multiple valid inputs, the next validated user can immediately follow the person in front of them. The door may remain open between each user access.

| | INDICATION | CONDITION | ACTION |
|----------|----------------|--|----------------|
| LED's: | Red | Armed | Do Not Proceed |
| | Flashing Red | In Use, Alarm/Tamper | Wait |
| | Green | Bypassed | Free Access |
| | Flashing Green | Valid User Access | Proceed |
| AUDIBLE: | Single Beep | Valid User Access | |
| | Continuous | Alarm/Tamper | |
| | Pulsing | Beam Block Warning (only when door switch is used) Door Propped (door held open over 10 seconds) | |

STEP BY STEP

- When approaching the Entry Sentry avoid intruding into the Detection Area **prior** to being granted access. Violating the Detection Area without access having been granted results in an Alarm, and may summon Security personnel.
- Present your User Identification (Card, Badge, Biometric, etc.) as per the Access Control System manufacturer's instructions.
- After validation is received, the Entry Sentry will Beep and the Green LED will flash. You may proceed.
- Proceed directly through the doorway, Avoid loitering as this could cause an Alarm.
- Should no completed passage be detected the system will reset after a short time out period.
 You will need to re-validate with your User Identification to be granted passage after a time out.
- When Free Exit is enabled you may pass through the doorway in that direction without presenting User Identification.

800 272 3555



ES5200 SERIES - ENLARGED WIRING AND MOUNTING DRAWINGS

Note detail for orientation of electronics assembly in reference to the Mounting Plate for Door and Wall mount applications.





