

CERTIFICATE OF COMPLIANCE

Certificate Number 20180418-R18515
Report Reference R18515-20110323
Issue Date 2018-APRIL-18

Issued to: DETEX CORPORATION
302 DETEX DR
NEW BRAUNFELS TX 78130

This is to certify that representative samples of FIRE EXIT HARDWARE
Refer to Addendum page for Models/Product


Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

Standard(s) for Safety: ANSI/UL 10B - Fire Tests of Door Assemblies
ANSI/UL 10C - Positive Pressure of Fire Tests of Door Assemblies
UL 305 - Standard for Safety for Panic Hardware
CAN/ULC-S104 - Standard Method for Fire Tests of Door Assemblies
CAN/ULC-S132 - Standard Method of Tests for Emergency Exit and Emergency Fire Exit Hardware

Additional Information: See the UL Online Certifications Directory at www.ul.com/database for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20180418-R18515
Report Reference R18515-20110323
Issue Date 2018-APRIL-18

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

USL, CNL Fire Exit Hardware, Advantex F60, F70 and F80 Series concealed vertical rods for use on standard and double egress pairs of doors, rated up to and including 3 hrs (excluding 20 minute wood core doors), not exceeding 96 in. in width and 120 in. in height:

Model Designations:

Advantex Series F60 (consisting of Models F60, F61, F62, F63)


Advantex Series F70 (consisting of Models F70, F71)

Advantex Series F80 (consisting of Models F80, F81, F82, F83, F87, TF87)

All device models may be suffixed with FC, EA, ED, EE, EI, EM, ER, ES, EX, EXV, H, LD, EDxEX, EExER, ERxEX, EXxW, or TRO.

Model F62 may be suffixed with GB17

Model F63 may be suffixed with GB17



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

