

# VALUE SERIES® V40 SERIES (RIM)

## RATING

For no rating, leave blank

"H" = Hurricane

"F" = Fire Rated (Less/No Dogging Only)

"FH" = Hurricane and Fire Rated

## OUTSIDE TRIM FINISH

626 = Brushed chrome (D/WS trims)

628 = Brushed Aluminum (P/PN trims)

689 = Aluminum (BN/A/AN trims)

693 = Black, powder coated (BN/A/AN trims)

711 = Black, Aluminum (P/PN trims)

## DOGGING FUNCTION

LD = Less/No dogging

HD = Hex key dogging

CD = Cylinder key dogging

## STRIKES

98 = Semi-Mortise (std. on V40xNS)

99 = Surface (std. on V40)

94 = Double-Door (least secure)

## PRE-INSTALLED CYLINDERS

If cylinders provided by others, leave blank

MC65 = Mortise Cylinder(s) 6pin/Keyed 5

IC7 = Mortise Cylinder(s) SFIC housing

IK7 = Mortise Cylinder(s) InstaKey housing

RC65 = Rim Cylinder(s) 6pin/Keyed 5

IC7R = Rim Cylinder(s) SFIC housing

IK7R = Rim Cylinder(s) InstaKey housing

Specify KA for Keyed Alike

## PUSHPAD COLOR

Contact factory for other languages and colors

BLK = Black

RWE = Red Pushpad / White English Lettering

## POWER TRANSFERS

FC3 = 3' Flex Conduit

FC10 = 10' Flex Conduit

PT5 = Power Transfer

EH8 = Electric Hinge

## SERIES TYPE

V40 = Rim device, wide stile

V40xNS = Rim device, narrow stile

## DEVICE FINISH

628 = Brushed Aluminum\*

711 = Black, Aluminum

## KEYSTOP

For no keystone, leave blank

KS = Keystop (Available with EA, EB, EE, EI functions)

## DOOR WIDTH

36" wide door (3')\*

48" wide door (4')

## FASTENERS

For Standard machine, wood & self-drilling screws, leave blank

SN1 = Sex Nuts/Throughbolts (Hurricane rated hardware includes sex nuts for latch bolt)

## OUTSIDE TRIM FUNCTION & FINISH

01P = Exit only, blank plate

03P = Key retracts latch

01PN = Exit only, blank plate; narrow trim

03PN = Key retracts latch; narrow trim

03WS = Key retracts latch

02A = Dummy pull

03A = Key retracts pull; pull trim

02AN = Dummy pull; narrow trim

03AN = Key retracts pull - pull trim; narrow trim

02BN = Dummy lever; narrow trim

08BN = Active lever, key locks/unlocks lever; narrow trim (handed) (classroom)

09BN = Lever trim active by key, locked when key removed; narrow trim (handed) (storeroom)

14BN = Active lever, no key cylinder; narrow trim (handed) (passage)

02D2W = Dummy lever; wide trim (two posts for use with narrow head device)

08D2W = Active lever, key locks/unlocks lever; wide trim (two posts for use with narrow head device) (classroom)

09D2W = Lever trim active by key, locked when key removed; wide trim (two posts for use with narrow head device) (storeroom)

14D2W = Active lever, no key cylinder; wide trim (two posts for use with narrow head device) (passage)

EU2W = Electric lock/unlock; wide trim (two posts for use with narrow head device) - 24VDC & Fail Secure (FSE) Std. - Specify handing (not field reversible). For 12VDC specify VDC. For Fail Safe specify FSA

CBK = Cylinder Bracket Kit, 03 only, plate & pull handle by others required

## DOOR HANDING

RHR = Right hand reverse\*

LHR = Left hand reverse

## ELECTRIFIED FUNCTION

For no electrified function, leave blank

### Standard

Select Arming Time and Auto Rearm

EA = Hardwired Electric Alarm

(Formerly EH/EH R)

EB = Electric Alarm with Battery

ED = Electric Dogging

EX = Request To Exit (Signal) Switch

EXV = Request To Exit (Current) Switch

EI = Electric Integration (logic controller required)

ES = Electric Switching (dead latch & OKC switches)

### Delayed Egress

Select Arming Delay, Delayed Egress

Time and Silent Arming

EE = Delayed Egress

### Delayed Egress Only (EE)

Comes standard with 90-800 power supply

Single = (1) 90-800 w/o bat backup

Pair = (1) 90-800 w/o bat backup

### Latch Retraction

ER EX = Electric Latch Retraction with Request To Exit Switch (silencer standard)

### Latch Retraction Only (ER EX)

(Sold Separately)

Single = 81-800

Pair = 82-800

2 Single = 83-800

Fire-rated trims must be Fail Safe (FSA)

All fire-rated devices Less Dogging/fail safe

NOTE: \* = default/standard

Also see online version at [detex.com/hto](http://detex.com/hto)

January 10, 2024



Detex products can expose you to chemicals including Chromium (hexavalent compounds) and Lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.detex.com/prop65](http://www.detex.com/prop65)

# VALUE SERIES® V40xW SERIES (RIM, WEATHERIZED)



## RATING

For no rating, leave blank  
 "H" = Hurricane  
 "F" = Fire Rated (Less/No Dogging Only)  
 "FH" = Hurricane and Fire Rated

## OUTSIDE TRIM FINISH

626 = Brushed chrome (D/WS trims)  
 628 = Brushed Aluminum (P/PN trims)  
 689 = Aluminum (BN/A/AN trims)  
 693 = Black, powder coated (BN/A/AN trims)  
 711 = Black, Aluminum (P/PN trims)

## DOGGING FUNCTION

LD = Less/No dogging  
 HD = Hex key dogging  
 CD = Cylinder key dogging

## PRE-INSTALLED CYLINDERS

If cylinders provided by others, leave blank  
 MC65 = Mortise Cylinder(s) 6pin/Keyed 5  
 IC7 = Mortise Cylinder(s) SFIC housing  
 IK7 = Mortise Cylinder(s) InstaKey housing  
 RC65 = Rim Cylinder(s) 6pin/Keyed 5  
 IC7R = Rim Cylinder(s) SFIC housing  
 IK7R = Rim Cylinder(s) InstaKey housing

## POWER TRANSFERS

FC3W = 3' Weatherized Flex Conduit  
 FC10W = 10' Weatherized Flex Conduit  
 PT5 = Power Transfer  
 EH8 = Electric Hinge

## SERIES TYPE

V40xW = Weatherized Rim device, wide stile (non-electrified)  
 V40xNSxW = Weatherized Rim device, narrow stile (non-electrified)

## DEVICE FINISH

628 = Brushed Aluminum\*  
 711 = Black, Aluminum

## STRIKES

98 = Semi-Mortise (std. on V40xNS)  
 99 = Surface (std. on V40)  
 94 = Double-Door (least secure)

## PUSHPAD COLOR

Contact factory for other languages and colors  
 BLK = Black  
 RWE = Red Pushpad / White English Lettering

## OUTSIDE TRIM FUNCTION & FINISH

01P = Exit only, blank plate  
 03P = Key retracts latch  
 01PN = Exit only, blank plate; narrow trim  
 03PN = Key retracts latch; narrow trim  
 03WS = Key retracts latch  
 02A = Dummy pull  
 03A = Key retracts pull; pull trim  
 02AN = Dummy pull; narrow trim  
 03AN = Key retracts pull - pull trim; narrow trim  
 02BN = Dummy lever; narrow trim  
 08BN = Active lever, key locks/unlocks lever; narrow trim (handed) (classroom)  
 09BN = Lever trim active by key, locked when key removed; narrow trim (handed) (storeroom)  
 14BN = Active lever, no key cylinder; narrow trim (handed) (passage)  
 02D2W = Dummy lever; wide trim (two posts for use with narrow head device)  
 08D2W = Active lever, key locks/unlocks lever; wide trim (two posts for use with narrow head device) (classroom)  
 09D2W = Lever trim active by key, locked when key removed; wide trim (two posts for use with narrow head device) (storeroom)  
 14D2W = Active lever, no key cylinder; wide trim (two posts for use with narrow head device) (passage)  
 EU2W = Electric lock/unlock; wide trim (two posts for use with narrow head device) - 24VDC & Fail Secure (FSE) Std. - Specify handing (not field reversible). For 12VDC specify VDC. For Fail Safe specify FSA  
 CBK = Cylinder Bracket Kit, 03 only, plate & pull handle by others required

## DOOR HANDING

RHR = Right hand reverse\*  
 LHR = Left hand reverse

## ELECTRIFIED FUNCTION

For no electrified function, leave blank

### Weatherized Alarms

Select Arming Time and Auto Rearm  
 EB W = Electric Battery Operated Exit Alarm Weatherized

### Latch Retraction

ER EX W = Electric Latch Retraction Weatherized with Request To Exit Switch (silencer standard)

### Latch Retraction Only (ER EX W)

(Sold Separately)  
 Single = 81-800  
 Pair = 82-800  
 2 Single = 83-800

### Weatherized Others

ER EX W = Electric Latch Retraction Weatherized with Request To Exit Switch (silencer standard)  
 EX W = Request To Exit (Signal) Switch Weatherized  
 EXV W = Request To Exit (Current) Switch Weatherized  
 WDE = Weatherized Delayed Egress (see EasyKits)

## KEYSTOP

For no keystone, leave blank  
 KS = Keystop (Available with EB W function)

## DOOR WIDTH

36" wide door (3')\*  
 48" wide door (4')

## FASTENERS

For Standard machine, wood & self-drilling screws, leave blank  
 SN1 = Sex Nuts/Throughbolts (Hurricane rated hardware includes sex nuts for latch bolt)

Fire-rated trims must be Fail Safe (FSA)

All fire-rated devices Less Dogging/fail safe

NOTE: \* = default/standard

Also see online version at [detex.com/hto](http://detex.com/hto)

April 22, 2020



Detex products can expose you to chemicals including Chromium (hexavalent compounds) and Lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.detex.com/prop65](http://www.detex.com/prop65)

# VALUE SERIES® V50/V51 SERIES (SURFACE VERTICAL ROD)

## RATING

For no rating, leave blank

"H" = Hurricane (V50 & V50xW only)

"F" = Fire Rated (Less/No Dogging Only)

"FH" = Hurricane and Fire Rated

## STRIKES

**96** = Surface non-roller top strike and non-dust proof bottom strike\*

**96B** = Substitute 96 bottom strike for Dust Proof strike

## PUSHPAD COLOR

Contact factory for other languages and colors

**BLK** = Black

**RWE** = Red Pushpad / White English Lettering

## SERIES TYPE

**V50** = SVR, wide stile

**V50xNS** = SVR, narrow stile

**V51** = SVR, top rod only, wide stile

**V51xNS** = SVR, top rod only, narrow stile

## OUTSIDE TRIM FINISH

**626** = Brushed chrome (D/WS trims)

**628** = Brushed Aluminum (P/PN trims)

**689** = Aluminum (BN/A/AN trims)

**693** = Black, powder coated (BN/A/AN trims)

**711** = Black, Aluminum (P/PN trims)

## DOGGING FUNCTION

**LD** = Less/No dogging

**HD** = Hex key dogging

**CD** = Cylinder key dogging

## DEVICE FINISH

**628** = Brushed Aluminum\*

**711** = Black, Aluminum

## PRE-INSTALLED CYLINDERS

If cylinders provided by others, leave blank

**MC65** = Mortise Cylinder(s) 6pin/Keyed 5

**IC7** = Mortise Cylinder(s) IC housing

**IK7** = Mortise Cylinder(s) InstaKey housing

**RC65** = Rim Cylinder(s) 6pin/Keyed 5

**IC7R** = Rim Cylinder(s) IC housing

**IK7R** = Rim Cylinder(s) InstaKey housing

Specify KA for Keyed Alike

Trim

Device

## POWER TRANSFERS

**FC3** = 3' Flex Conduit

**FC10** = 10' Flex Conduit

**PT5** = Power Transfer

**EH8** = Electric Hinge

## OUTSIDE TRIM STYLE & FINISH

**01P** = Exit only, blank plate

**03P** = Key retracts latch

**01PN** = Exit only, blank plate; narrow trim

**03PN** = Key retracts latch; narrow trim

**03WS** = Key retracts latch

**02A** = Dummy pull

**03A** = Key retracts pull; pull trim

**02AN** = Dummy pull; narrow trim

**03AN** = Key retracts pull - pull trim; narrow trim

**02BN** = Dummy lever; narrow trim

**08BN** = Active lever, key locks/unlocks lever; narrow trim (handed) (classroom)

**09BN** = Lever trim active by key, locked when key removed; narrow trim (handed) (storeroom)

**14BN** = Active lever, no key cylinder; narrow trim (handed) (passage)

**02D2W** = Dummy lever; wide trim (two posts for use with narrow head device)

**08D2W** = Active lever, key locks/unlocks lever; wide trim (two posts for use with narrow head device) (classroom)

**09D2W** = Lever trim active by key, locked when key removed; wide trim (two posts for use with narrow head device) (storeroom)

**14D2W** = Active lever, no key cylinder; wide trim (two posts for use with narrow head device) (passage)

**EU2W** = Electric lock/unlock; wide trim (two posts for use with narrow head device) (24VDC & Fail Secure [FSE] Std.) - Specify handing (not field reversible). For 12VDC specify VDC. For Fail Safe specify FSA

**CBK** = Cylinder Bracket Kit, 03 only, plate & pull handle by others required

## DOOR HANDING

**RHR** = Right hand reverse\*

**LHR** = Left hand reverse

## KEYSTOP

**KS** = Keystop (Available with EA, EE, EE ER, EI functions)

## DOOR WIDTH

**36"** wide door (3')\*

**48"** wide door (4')

## DOOR HEIGHT/SVR HEIGHT

**84"** high door

**96"** high door

**120"** high door

## FASTENERS

For Standard machine, wood & self-drilling screws, leave blank

**SN1** = Sex Nuts/Throughbolts (Hurricane rated hardware includes sex nuts for top latch and bottom bolt)

## ELECTRIFIED FUNCTION

For no electrified function, leave blank

### Standard

Select Arming Time and Auto Rearm

**EA** = Hardwired Electric Alarm (Formerly EH/EH R)

**EB** = Electric Alarm with Battery

**ED** = Electric Dogging

**EX** = Request To Exit (Signal) Switch

**EXV** = Request To Exit (Current) Switch

### Delayed Egress

Select Arming Delay, Delayed Egress Time and Silent Arming

**EE** = Delayed Egress

### Delayed Egress Only (EE)

Comes standard with 90-800 power supply

**Single** = (1) 90-800 w/o bat backup

**Pair** = (1) 90-800 w/o bat backup

### Latch Retraction

**ER EX** = Electric Latch Retraction with

Request To Exit Switch (silencer standard)

### Latch Retraction Only (ER EX)

(Sold Separately)

**Single** = 81-800

**Pair** = 82-800

**2 Single** = 83-800

Fire-rated trims must be Fail Safe (FSA)

All fire-rated devices Less Dogging/fail safe

NOTE: \* = default/standard

Also see online version at [detex.com/hto](http://detex.com/hto)

April 22, 2020



Detex products can expose you to chemicals including Chromium (hexavalent compounds) and Lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.detex.com/prop65](http://www.detex.com/prop65)

# VALUE SERIES® V50xW/V51xW SERIES (SURFACE VERTICAL ROD, WEATHERIZED)



## RATING

For no rating, leave blank

"H" = Hurricane (V50 & V50xW only)

"F" = Fire Rated (Less/No Dogging Only)

"FH" = Hurricane and Fire Rated

## SERIES TYPE

**V50xW** = Weatherized SVR, wide stile (non-electrified)

**V50xNSxW** = Weatherized SVR, narrow stile (non-electrified)

**V51xW** = Weatherized SVR, top rod only, wide stile (non-electrified)

**V51xNSxW** = Weatherized SVR, top rod only, narrow stile (non-electrified)

## OUTSIDE TRIM FINISH

**626** = Brushed chrome (D/WS trims)

**628** = Brushed Aluminum (P/PN trims)

**689** = Aluminum (BN/A/AN trims)

**693** = Black, powder coated (BN/A/AN trims)

**711** = Black, Aluminum (P/PN trims)

## DOGGING FUNCTION

**LD** = Less/No dogging

**HD** = Hex key dogging

**CD** = Cylinder key dogging

## DEVICE FINISH

**628** = Brushed Aluminum\*

**711** = Black, Aluminum

## STRIKES

**96** = Surface non-roller top strike and non-dust proof bottom strike\*

**96B** = Substitute 96 bottom strike for Dust Proof strike

## PRE-INSTALLED CYLINDERS

If cylinders provided by others, leave blank

**MC65** = Mortise Cylinder(s) 6pin/Keyed 5

**IC7** = Mortise Cylinder(s) IC housing

**IK7** = Mortise Cylinder(s) InstaKey housing

**RC65** = Rim Cylinder(s) 6pin/Keyed 5

**IC7R** = Rim Cylinder(s) IC housing

**IK7R** = Rim Cylinder(s) InstaKey housing

Specify KA for Keyed Alike

Trim

Device

## PUSHPAD COLOR

Contact factory for other languages and colors

**BLK** = Black

**RWE** = Red Pushpad / White English Lettering

## POWER TRANSFERS

**FC3W** = 3' Weatherized Flex Conduit

**FC10W** = 10' Weatherized Flex Conduit

**PT5** = Power Transfer

**EH8** = Electric Hinge

## OUTSIDE TRIM STYLE & FINISH

**01P** = Exit only, blank plate

**03P** = Key retracts latch

**01PN** = Exit only, blank plate; narrow trim

**03PN** = Key retracts latch; narrow trim

**03WS** = Key retracts latch

**02A** = Dummy pull

**03A** = Key retracts pull; pull trim

**02AN** = Dummy pull; narrow trim

**03AN** = Key retracts pull - pull trim; narrow trim

**02BN** = Dummy lever; narrow trim

**08BN** = Active lever, key locks/unlocks lever; narrow trim (handed) (classroom)

**09BN** = Lever trim active by key, locked when key removed; narrow trim (handed) (storeroom)

**14BN** = Active lever, no key cylinder; narrow trim (handed) (passage)

**02D2W** = Dummy lever; wide trim (two posts for use with narrow head device)

**08D2W** = Active lever, key locks/unlocks lever; wide trim (two posts for use with narrow head device) (classroom)

**09D2W** = Lever trim active by key, locked when key removed; wide trim (two posts for use with narrow head device) (storeroom)

**14D2W** = Active lever, no key cylinder; wide trim (two posts for use with narrow head device) (passage)

**EU2W** = Electric lock/unlock; wide trim (two posts for use with narrow head device) (24VDC & Fail Secure [FSE] Std.) - Specify handing (not field reversible). For 12VDC specify VDC. For Fail Safe specify FSA

**CBK** = Cylinder Bracket Kit, 03 only, plate & pull handle by others required

## DOOR HANDING

**RHR** = Right hand reverse\*

**LHR** = Left hand reverse

## KEYSTOP

**KS** = Keystop (Available with EB W function)

## DOOR WIDTH

**36"** wide door (3')\*

**48"** wide door (4')

## DOOR HEIGHT/SVR HEIGHT

**84"** high door

**96"** high door

**120"** high door

## FASTENERS

For Standard machine, wood & self-drilling screws, leave blank

**SN1** = Sex Nuts/Throughbolts (Hurricane rated hardware includes sex nuts for top latch and bottom bolt)

## ELECTRIFIED FUNCTION

For no electrified function, leave blank

### Weatherized Alarms

Select Arming Time and Auto Rearm

**EB W** = Electric Battery Operated Exit Alarm Weatherized

### Latch Retraction

**ER EX** = Electric Latch Retraction with Request To Exit Switch (silencer standard)

**ER EX W** = Electric Latch Retraction Weatherized with Request To Exit Switch (silencer standard)

### Latch Retraction Only (ER)

(Sold Separately)

**Single** = 81-800

**Pair** = 82-800

**2 Single** = 83-800

### Weatherized Others

**ER EX W** = Electric Latch Retraction Weatherized with Request To Exit Switch (silencer standard)

**EX W** = Request To Exit (Signal) Switch Weatherized

**EXV W** = Request To Exit (Current) Switch Weatherized

**WDE** = Weatherized Delayed Egress (see EasyKits)

Fire-rated trims must be Fail Safe (FSA)

All fire-rated devices Less Dogging/fail safe

NOTE: \* = default/standard

Also see online version at [detex.com/hto](http://detex.com/hto)

April 22, 2020



Detex products can expose you to chemicals including Chromium (hexavalent compounds) and Lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.detex.com/prop65](http://www.detex.com/prop65)