AO19 SERIES®

AO19 Activation Switches

4 1/2" Round Push Plate Switches

The 104742-X switches combine architectural quality finishes with industrial grade components to provide attractive and reliable automatic door activation.



Benefits

Bononto		
The 104742 Series push plate switches are designed to provide reliable activation of any automatic door.	 Designed as a universal switch, the 104742 Series fit single-gang electrical boxes with no adapters necessary. 	 Each unit is built utilizing heavy gauge stainless steel, aircraft quality rivets and screws.
		 The most reliable microswitch in
	Durable finishes.	the industry.
• The 104742 Series features 4" round face plates in either stainless	• 4" All Active Face Plate.	 Rubber "Bellows" increases weather protection (included).
steel or blue powder coated	• H 4 1/2" Formed Stainless Steel	
aluminum with etched and paint- filled legends.	Back Plate.	 Fits single or 2-gang Electrical Box, 104738-1025 Surface Mount
	 A surface mount box is also 	Box, or 104753-R4 Mounting Box
 Includes tamper-resistant screws. 	available. 104738-1025	With Transmitter.

Electrical Options

Radio Control Versions Available

Accessories

• 104738-1025 mounting box



• 104752 Multi-Mode Receivers



- 104753-R4 Mounting Box with Transmitter
- 104753-STX-R4




Technical Information

• 4" All Active Face Plate

• 4 1/2" Formed Stainless Steel Back Plate

Riser Diagram



• UL Listed Momentary Switch, SPDT, 15 Amp @ 125V AC Rubber "Bellows" increases weather protection (included)

Listings and Approvals



American National Standards Institute (ANSI)



Building Hardware Manufacturers Association (BHMA) - ANSI/BHMA A156.10 & A156.19




UL Approved Switches

Warranty

1 Year Limited Manufacturer's Warranty







Detex Corporation 302 Detex Drive New Braunfels, Texas 78130-3045 USA PH. (830) 629-2900 (800) 729-3839 FAX (800) 653-3839 http://www.detex.com USA Sales: marketing@detex.com International Sales: export@detex.com

A Cancer & Reproductive Harm - www.detex.com/prop65