Series 800

80-800 / 90-800

Power Supply

The Detex 80-800 or 90-800 Power Supply is designed for applications requiring a continuous supply of a regulated, filtered output voltage. The Detex 80-800 Power Supply includes a battery charging circuit. Batteries provide backup for uninterrupted service.





80-800

90-800

Benefits

- Simplifies installations that do not require a conduit, Class 2 outputs standard and may be wired directly to 115VAC input
- Provides continuous regulated and filtered 12VDC or 24VDC (80-800); 24VDC (90-800)
- Designed specifically to support electric locks and access control systems
- Provides individual fused protection, field reset
- On/Off switch allows for easy service and inspection

Features

- Fire alarm input provides release of fail-safe locks in case of emergency (80-800/90-800)
- Field selectable outputs (80-800 only)
- Auto-resetting circuit protection (80-800/90-800)
- Battery charging circuit, PTC protection (80-800 only)
- LED system status indicator (80-800/90-800)
- Class 2 outputs (80-800/90-800)
- Heavy gauge enclosure, 18ga (80-800/90-800)
- Low battery disconnect when batteries are below 70% capacity (80-800 only)

Accessories

• Batteries (80-800 only)

Technical Information


- Input: 115VAC, 50/60 Hz
- Class 2 Rated

- 80-800 (1) Output: 12 or 24VDC,
- 90-800 (2) Outputs: 24VDC, 1A
- Battery Charger: 13.5/27VDC, 500mA (80-800 only)




- Painted Beige 80-800
- Painted Black 90-800


Dimensions (80-800)



Dimensions (90-800)



Riser Diagram



Listings and Approvals



Detex Limited Warranty

3 Year Limited Manufacturer's Warranty



Detex Corporation 302 Detex Drive New Braunfels, Texas 78130-3045 USA PH. (830) 629-2900 (800) 729-3839 FAX (800) 653-3839

http://www.detex.com **USA Sales:**

marketing@detex.com International Sales: export@detex.com