



82 SERIES 83 SERIES (Top Rod Only)


Concealed Vertical Rod Device - Wide Stile Aluminum Door

Designed to enhance the architectural aesthetics of any décor, the 82 and 83 Series **concealed vertical rod exit device** is also super-heavy-duty **panic and fire exit hardware** for use on all types of wide stile aluminum doors without a mullion. The patented mounting plate system ensures the easiest and most accurate installation of panic hardware available.

Note: For Top Rod Only -
Specify 83 Series

Also Available:

- 60/61 CVR Narrow Stile Alum. Door
- 62/63 CVR Narrow Stile H.M. Door
- 70/71 CVR Wide Stile Wood Door
- 80/81 CVR Wide Stile H.M. Door



Benefits

- Tough and durable design for years of trouble-free service in high-use, high-abuse environments
- Minimal door prep saves time and money
- Fast and easy installation saves time and money
- Heavy duty angled end cap deflects damage away from device
- Except for 03WSV, outside trims are easily changed or rekeyed without removing device from door

Features

- 6-position multi-step action in top latch keeps top and bottom bolts retracted until door closes and provides more consistent re-latching and security to door
- Top strike fully adjustable both vertically and to accommodate a variety of varying weather strip thicknesses
- Top strike both secures the door and re-engages the latchbolts
- Patented deadlocking of top (82 and 83 Series) and bottom bolt (82 Series) assemblies
- Durable steel bottom drop bolt (82 Series)
- Rods are easily adjustable with rods installed in door
- Handed - field reversible
- Field sizeable
- 1/8 turn dogging

Mechanical Options

- F - 3-Hour Fire Rated without astragal up to 10 foot (steel) door
 - AM - Anti-Microbial Coating
 - HD - Hex Dogging (Std.)
 - CD - Cylinder Dogging
 - SLR - Silencer
 - 24 - Fits 24" Door Width
 - 30 - Fits 30" Door Width
 - 36 - Fits 36" Door Width (Std.)
 - 48 - Fits 48" Door Width
 - EC1 - Heavy duty angled end cap (standard on 630, 606, 612, 613, 605, 611 & 629 finishes only)
 - EC2 - Flush end cap (standard on 628, 693 & 695 finishes only), specify when used on 2" - 3-1/2" stiles
- For full list of available mechanical options, see 80 Series How To Order page

Electrical Options

- Exit Alarm (EA)
 - Electric Dogging (ED)
 - Delayed Egress Self-Contained (EE)
 - Electric Latch Retraction (ER)
 - Request to Exit (EX)
 - Request to Exit for High Voltage (EXV)
 - Electric Delayed Egress with Latch Retraction (EE ER)
- Refer to Electrified Options section for more information

Accessories

- SSK4- Security Torx Screw Kit
- Trim Functions (see Outside Trims)



Technical Information

• Door Types - Aluminum/
Aluminum Channel FRP

• Door Thickness - Fits standard
1-3/4" - 2-1/4" (for other door
thicknesses contact factory)

• Fasteners - Machine and Self-
Drilling Screws standard

• Door Stile - Fits minimum 4-1/2"

• Rail is heavy ribbed aluminum
extrusion


Finishes

605 / US3 Polished Brass
606 / US4 Brushed Brass
611 / US9 Polished Bronze
612 / US10 Brushed Bronze
613 / US10B Oil Rubbed Bronze


628 / US28 Satin Aluminum
629 / US32 Polished Stainless
Steel
630 / US32D Brushed Stainless
Steel

693 / SPBLK Black, painted
695 / SP313 Dark Bronze, painted


Top & Bottom Latch Door Prep for 82 & 83 Series




Top Latch Installation for 82 & 83 Series




Top Strike Installation for 82 & 83 Series



Bottom Latch Installation for 83 Series only



Dimensions



Detex Limited Warranty

10 Year Mechanical/3 year Electrical
Limited Manufacturer's Warranty

Listings and Approvals



UL Listed Panic Hardware



ULC 97, Standard 7-2 and
UL10B/UL10C for positive
pressure



UL Listed Fire Exit Hardware
for 3 hours, maximum 8'x10'
pairs of doors



ANSI/BHMA certified A156.3



Meets ADA requirements



Meets NFPA 80 & 101 for Life
Safety

For detailed fire listings, visit www.detex.com/PROVEN

Cancer & Reproductive Harm - www.detex.com/prop65

Where Trust is Built™
DETEX®
Life Safety and Security Door Hardware

Detex Corporation
302 Detex Drive
New Braunfels, Texas 78130-3045 USA
PH. (830) 629-2900
(800) 729-3839
FAX (800) 653-3839
<http://www.detex.com>
USA Sales:
marketing@detex.com
International Sales:
export@detex.com