

EasyKit®

ACDx10ER ACDx40ER

Access Controlled Doors with Latch Retraction

The ACDx10ER EasyKit offers industry-proven life safety and security hardware for high-use, high-abuse doors with innovative, access control readers and software providing an easy-to-install, access control solution.



Also Included:

Outside Trim (Call Factory for Options)

Wiring Diagram

(Shown on 10 Series Rim Exit Device - Available with 10/40 Rim, 30 Mortise and 20/21/50/51 Surface Vertical Rod Devices)

Benefits

- Innovative, robust proximity technology allows for heavy access control applications
- Easy-to-install, heavy-duty hardware provides years of trouble-free, heavy access control use
- Easy-to-manage software tracks hundreds of users and cards
- Easily managed, add or delete users as needed, when necessary
- EasyKit includes all required hardware, wiring and riser diagrams for easy to order, easy to install, easy to use package
- Each kit is easily configured for entry read and/or exit read applications
- Minimal door and frame prep saves time and money

Features

- Kit includes, Power supplies, Controllers, Latch Retraction exit device with trim, 2 access control readers, cards and basic software
- Stainless steel deadlocking Pullman-type latch bolt on exit device
- Non-handed exit hardware
- Heavy-duty angled end cap deflects damage away from panic device

Mechanical Options

- 36 - Fits 36" door width (Std.)
- 48 - Fits 48" door width
- F - 3 hour fire rated exit device
- H - Hurricane Rated exit device
- 99 - surface strike (Std.)
- 98 - semi mortise strike

Electrical Options

- Request to Exit (EX) pushpad switch for remote signaling upon exit
- M12 - Power Supply 12V module for other low volt accessories
- LBM - Latch Bolt Monitor
- FC - Flex Conduit and End Cap
- PT5 - Power Transfer
- EWH8-626 - Electric Hinge

DETEx®
A Century of Security
1923-2023

Accessories

- SN1 - Sex Nut Fasteners
- Various configurable cylinder trims, pulls and levers (Call factory for specific details)


Technical Information

- Door Types - Wood, Hollow Metal, Fiberglass or Aluminum
- Door Thickness - Fits standard 1-3/4" - 2-1/4" (for other door thicknesses, contact factory)
- Medium Stile - Wide stile rim and surface vertical rod fits minimum 5" stile with 99 strike (Std.)
- Narrow Stile - Narrow stile rim and surface vertical rod fits minimum 2" stile with 98 strike (optional)
- Machine and Sheet Metal Screws (Std.)
- Rail is heavy ribbed aluminum extrusion

Finishes (Advantex)

- 605 / US3 - Polished Brass
- 606 / US4 - Brushed Brass
- 611 / US9 - Polished Bronze
- 612 / US10 - Brushed Bronze
- 613 / US10B - Oil Rubbed Bronze
- 629 / US32 - Polished Stainless Steel
- 630 / US32D - Brushed Stainless Steel


Riser Diagram



Listings and Approvals - Advantex

- UL LISTED Panic Hardware
- UL LISTED Fire Exit Hardware for 3 hours, maximum
- UL LISTED 4x10" single doors and pairs of 4x8" with F90KR key removable Mullion
- Meets ADA requirements
- UBC 97, Standard 7-2 and UL10C for positive pressure
- BHMA ANSIBHMA certified A156.3
- NFPA Meets NFPA 80 & 101 for Life Safety
- Miami-Dade County NOA 10-0303.02 EXP. 04/07/15 State of Florida Approval FL9052 } 10 Series Only
- California State Fire Marshall - 4140-0127:105 and 3725-0127:108

Dimensions



10 Series Dimensions Shown



Cancer & Reproductive Harm - www.detex.com/prop65

DETEX[®]
A Century of Security
1923-2023

Detex Corporation
302 Detex Drive
New Braunfels, Texas 78130-3045 USA
PH. (830) 629-2900
(800) 729-3839
FAX (800) 653-3839
<http://www.detex.com>
USA Sales:
marketing@detex.com
International Sales:
export@detex.com