Tailgate Detection System

AT-5600 Series with Digital Voice Alarm

See the AT-5600 in action www.detex.com/videos

The Detex AT-5600 Series Tailgate Detection System assures that only one individual enters a secured doorway for each authorized card read; compatible with most card reader technologies the AT-5600 is easy to retrofit. This unique and cost effective optical security system, which uses unique algorithms and infrared sensor beams to detect tailgating, is perfectly suited for areas requiring tighter security. The potential applications for the AT-5600 are unlimited, however typical applications include employee entrances, computer rooms, bank vaults, dorm entrances, and areas with restricted access. Its subtle design does not distract from interior aesthetics and it mounts easily on standard door frames.





Local digital voice annunciator

For local alarm annunciator, see AT-5200 catalog page

Benefits

- Adds additional security to a restricted area where unauthorized entry must be controlled
- Integrated door prop alarm for additional security
- Compatible with most access control systems and easily retrofits, providing enhanced security
- High throughput easy entry or exit for authorized personnel
- Encourages employees, students, visitors, etc. to maintain access control procedures
- ADA compliant
- · Blends in with architectural styling

Features

- Local digital voice annunciator; unauthorized access/egress is annunciated locally and with the access control system
- Key switch for local alarm shunt/ override
- Alarm 3 seconds fixed time/auto reset
- Mounts on standard width door frame or wall (80" max width)

- Spacer mounting kit standard, can be used as a raceway for wiring
- Alarm can be reset by a remote contact
- Remote annunciator plates fit in a single gang box
- Status indicator lights (Wait or Proceed)
- Field configurable for card in/card out or card in/free exit operation
- Adjustable access period
- Alarm status relay for remote annunciation
- Tamper Switch




Mechanical Options

inconamour options		
Spacer Mounting Kit (order separately)	1 gang Remote Annunciator Plate (included with AT-5600-R1)	 Mullion Mount Remote Annunciator plate (specify AT-5600-R2)
Electrical Options		
MS-1039 Magnetic Door Contacts (optional)	 80-800 Power Supply (12VDC option) 	
Technical Information		
• 12 VDC @ 1 Amp	 Direct mounting to doorframe or wall by using optional spacer mounting kit 	 Voice Sound Level - 85dB @ 3 feet
Finishes	-	

Finishes

• Black with IR Plexiglass cover

Dimensions



Listings and Approvals



Meets ADA Requirements

Detex Limited Warranty

3 Year Limited Manufacturers Warranty



Detex Corporation 302 Detex Drive New Braunfels, Texas 78130-3045 USA PH. (830) 629-2900 (800) 729-3839 FAX (800) 653-3839 http://www.detex.com **USA Sales:** marketing@detex.com International Sales:

export@detex.com