

The Exit Alarm (EA) device option is designed for areas that require a stand-alone alarm on an emergency exit door. The alarm will sound when someone attempts to exit a door by depressing the pushpad, alerting management that violation has occurred. The internal alarm with remote signal and remote bypass capabilities is ideal for doors where both security and life safety are a concern.



Available with 10/40 Rim, 30 Mortise, 20/21/50/51 Surface Vertical Rod Devices and 60/61/62/63/70/71/80/81/82/83 Concealed Vertical Rod Devices

Benefits

- Controls foot traffic, deters unauthorized exits, prevents loss and meets building code requirements
- Reduces employee and customer theft
- One cylinder provides arming, disarming and dogging
- Fast and easy installation saves time and money
- Durable electronics provide years of trouble-free service, saving on replacement costs

Features

- Powered by standard 9-volt battery or 12V or 24V AC/DC power with 9-volt battery backup
- 100dB alarm
- State-of-the-art electronics offer reliable security and instantaneous alarm
- Arming delay Factory default is
 15 second delay after key reset.
 1 second or 5 second delays also available. Call factory
- Manual/Auto Rearming Factory default is field-selectable for manual key arming or 2 minute auto rearm.
 10 minute and 20 minute auto rearm also available. Call Factory
- Mortise cylinder key switch arming
- Through-wire hinge or power transfer compatible
- Low Battery Alert (Audible/Visual)
- Visual and audible arming indicators

Mechanical Options

- CD Cylinder Dogging
- LD Less Dogging
- SLR Silencer
- KS Key Stop (Key removed only when armed)
- Add to existing 10/20/21/30/40/50/51 device by adding EA slide-in filler (specify finish and door width)
- FC3EC1 Flexible 3' Conduit Kit, includes EC1 ramped end cap (specify finish)
- FC3EC2 Flexible 3' Conduit Kit, includes EC2 flush end cap (specify finish)
- FC10EC1 Flexible 10' Conduit Kit, includes EC1 ramped end cap (specify finish)
- FC10EC2 Flexible 10' Conduit Kit, includes EC2 flush end cap (specify finish)

- PT5 Concealed mortise mount power transfer
- EH8 Five-knuckle energy transfer hinge - 8 wires

For full list of available mechanical options, see individual device how to order page



Accessories

• MC65 - Factory Installed Mortise Cylinder

· Optional Cylinder Nut Wrench P/N: 103779


• PP-5152-3 - 12 VAC Transformer

• PP-5152-2 - 24 VAC Transformer


Device Finishes

605 / US3	Polished Brass	628 / US28	Aluminum Satin	693 / SPBLK Black, Painted
606 / US4	Brushed Brass	629 / US32	Polished Stainless	695 / SP 313 Dark Bronze, Painted
611 / US9	Polished Bronze		Steel	
612 / US10	Brushed Bronze	630 / US32D	Brushed Stainless	
613 / US10B	Oil Rubbed Bronze		Steel	

Riser Diagram



Power Connections



Listings and Approvals

See individual device (i.e. 10 Series) catalog page for fire and panic listings and windstorm ratings/ approvals

Detex Limited Warranty

10 Year Mechanical/3 Year Electrical Limited Manufacturer's Warranty



Detex Corporation 302 Detex Drive New Braunfels, Texas 78130-3045 USA PH. (830) 629-2900 (800) 729-3839 FAX (800) 653-3839 http://www.detex.com **USA Sales:** marketing@detex.com International Sales: export@detex.com