MAGNETIC SWITCH MS-2049F, MS-2049S, MS-2049SC, MS-2049SI

These magnetic switches are designed primarily to serve as sensing devices to detect the opening of a door or window; to assure that a protected door is securely under surveillance; to serve as a trigger for a wall-mounted Detex Exit Alarm; to signal that a door has been inadvertently left open; and to be used as a direct switch to set off many kinds of audio and visual alarms.



MS-2049F Flush Magnetic Switch



MS-2049S Surface Mounted Magnetic Switch



MS-2049SC Surface Mounted **Magnetic Switch** with conduit connector for use with thin-wall conduit



MS-2049SI Surface Mounted Magnetic Switch for In-Swinging Doors

• UL listed for use on fire rated

doors and assemblies

|--|

· Provides assurance that protected doors are under surveillance

Features

- Tamper protection mounting screws inaccessible when door closed
- Components potted to protect against shock and moisture
- Wide range of alarm and signal • Easy installation with concealed wiring and color coded leads applications · Surface mounted units are housed Minimizes false signals due to in a durable high impact ABS loosely closed doors thermoplastic, a UL listed material Switch rated for over one million used in the manufacture of operations under load telephones, auto bodies, etc.

· Serves as a trigger for alarms or

remote monitors

Technical Information		
Maximum contact ratings - 24VDC @ .5A	 Overhead (preferred) or latch-stile mounting available for all models 	 The flush device (MS-2049F) should have the switch contact housed in the door frame and the magnet mortised in the edge of the door
 For use on steel, aluminum or wood doors and frames 	 Switch - single pole, double throw (SPDT) 	
 May be mounted on stiles as narrow as 1-3/8" 		 Wiring leads, 12" long, color coded, concealed



Dimensions (MS-2049F)

Riser Diagram



6"

Ο

6"

Λ

Latch edge

mounting



Overhead Installation, Front View

Dimensions (MS-2049S)



Front View



Overhead Installation, Side View



Side View

Listings and Approvals



"UL Listed Miscellaneous Fire Door Accessories" "UL Listed Door Position Switch"

Detex Limited Warranty

3 Year Limited Manufacturers Warranty



Detex Corporation 302 Detex Drive New Braunfels, Texas 78130-3045 USA PH. (830) 629-2900 (800) 729-3839 FAX (800) 653-3839 http://www.detex.com USA Sales: marketing@detex.com International Sales: export@detex.com

A Cancer & Reproductive Harm - www.detex.com/prop65