

# ADVANTEX® 20xW/21xW SERIES (WIDE SURFACE VERTICAL ROD, WEATHERIZED)



**RATING**  
 For no rating, leave blank  
**H** = Hurricane Rated  
**F** = Fire Rated (Less/No Dogging Only) - Fire pin included for F21  
**FH** = Hurricane and Fire Rated

**KNURLING**  
 For no knurling, leave blank  
**KN** = Knurled (lever trim only)

**SERIES TYPE**  
**20xW** = Weatherized SVR, wide stile (non-electrified)  
**21xW** = Weatherized SVR, top rod only, wide stile (non-electrified)

**OUTSIDE TRIM / DEVICE FINISH**

- 605** = Polished brass (PVD)
- 606** = Brushed brass (PVD)
- 611** = Polished bronze (PVD)
- 612** = Brushed bronze (PVD)
- 613** = Oil rubbed bronze
- 625** = Polished chrome
- 626** = Brushed chrome (std. on lever trims)
- 628** = Aluminum, powder coated (device only)
- 629** = Polished stainless steel
- 630** = Brushed stainless steel (std. on pull trims & device)
- 693** = Black, powder coated
- 695** = Dark bronze, powder coated

**DOGGING FUNCTION**  
**LD** = Less/No dogging  
**HD** = Hex key dogging  
**CD** = Cylinder key dogging

**STRIKES**  
**97** = Surface

**PRE-INSTALLED CYLINDERS**  
 If cylinders provided by others, leave blank  
**MC65** = Mortise Cylinder(s) 6pin/Keyed 5  
**IC7** = Mortise Cylinder(s) SFIC housing  
**IK7** = Mortise Cylinder(s) InstaKey housing  
**RC65** = Rim Cylinder(s) 6pin/Keyed 5  
**IC7R** = Rim Cylinder(s) SFIC housing  
**IK7R** = Rim Cylinder(s) InstaKey housing

**ANTIMICROBIAL**  
 For no coating, leave blank  
**AM** = Antimicrobial Coating

**FASTENERS**  
 For standard machine, wood & self-drilling screws, leave blank  
**SN1** = Sex Nuts/Throughbolts

**SILENCER**  
 For standard pushpad, leave blank  
**SLR** = Silent Latch & Pushpad

**OUTSIDE TRIM FUNCTION**

- For no outside trim, leave blank
- 01C** = Exit only, blank plate
  - 01W** = Dummy pull trim, Wide blank plate - long
  - 02C** = Dummy pull trim
  - 02Z** = Inactive Vandal pull handle (handed)
  - 03C** = Key retracts latch; pull trim
  - 03Z** = Key retracts latch; Vandal pull handle (handed)
  - 03W** = Key retracts latch; wide plate - long
  - 03WS** = Key retracts latch; plate - short
  - 01D** = Blank escutcheon; Wide lever handle (handed) (J, Q, S, T, U or FSB1076 lever)\*\*
  - 02D** = Dummy lever trim
  - 08D** = Active lever, key locks / unlocks lever; Wide lever handle (handed) (J, Q, S, T, U or FSB1076 lever\*\*) (classroom)
  - 09D** = Lever trim active by key, locked when key removed; Wide lever handle (handed) (J, Q, S, T, U or FSB1076 lever\*\*) (storeroom)
  - 14D** = Active lever, no key cylinder; Wide lever handle (handed) (J, Q, S, T, U or FSB1076 lever\*\*) (passage)
  - CBK** = Cylinder bracket kit, 03 only, plate & pull handle by others required
  - EU** = Electric Unlock Trim (24VDC & Fail Secure [FSE] Std.) - Specify handing (not field reversible). For 12VDC specify 12VDC. For Fail Safe specify FSA

**DOOR HANDING**  
**RHR** = Right hand reverse\*  
**LHR** = Left hand reverse

**KEYSTOP**  
 For no keystone, leave blank  
**KS** = Keystop (Available with EB W functions)

**ELECTRIFIED FUNCTION**

For no electrified function, leave blank

- Weatherized Alarms**  
 Select Arming Time and Auto Rearm
- EB W** = Electric Battery Operated Exit Alarm Weatherized
  - EB EX W** = Electric Battery Operated Exit Alarm Weatherized with Request To Exit (Signal) Switch
  - EB EXV W** = Electric Battery Operated Exit Alarm Weatherized with Request To Exit (3Amp Current) Switch

**Latch Retraction**  
**ER EX W** = Electric Latch Retraction Weatherized with Request To Exit Switch (silencer standard)

**Power Supply / Controller for Latch Retraction Only (ER EX W)**  
 Order/Sold Separately  
**Single = 81-800**  
**Pair = 82-800**  
**2 Independent Singles = 83-800**

**Weatherized Others**

- ER EX W** = Electric Latch Retraction Weatherized with Request To Exit Switch (silencer standard)
- EX W** = Request To Exit (Signal) Switch Weatherized
- EXV W** = Request To Exit (3Amp Current) Switch Weatherized
- WDE** = Weatherized Delayed Egress (see EasyKits)

**DOOR HEIGHT/SVR HEIGHT**  
 For 84" door heights, leave blank  
**84"** high door  
**96"** high door  
**120"** high door

**DOOR WIDTH**  
**24"** wide door  
**30"** wide door  
**36"** wide door (3')\*  
**48"** wide door (4')

**ENDCAP**  
**EC1** = Ramped endcap\*  
**EC2** = Flush endcap

**POWER TRANSFERS**  
 For no power transfers, leave blank

- FC3W** = 3' Weatherized Flex Conduit
- FC10W** = 10' Weatherized Flex Conduit
- PT5** = Power Transfer
- EH8** = Electric Hinge

Fire-rated trims must be fail safe (FSA)

\*\*Other FSB levers available: 1016, 1035, 1058, 1075, 1093, 1119, 1147. FSB levers available in 630 finish only. See catalog pages for more information.

NOTE: \* = default/standard

Also see online version at [detex.com/hto](http://detex.com/hto)

May 11, 2020

