A019 SERIES®

AO19 Hardwired Touchless Activation Accessories (NXG-IR-A)

The hands-free operation of the touchless activation accessories make them ideal for ADA applications and locations where hygiene is important, such as operating rooms, clean rooms, and other healthcare facilities. The Touchless Activation Switch is not recommended for outdoor use.



NXG-IR-A NexGen Infrared Hardwired Touchless Activation Switch

Benefits

 The touchless switch requires no touch to activate, ideal for ADA applications

Features

- Adjustable operating range from 5-12"
- NexGen technology using rapid infrared pulses, to ensure accurate detection
- Adjustable response/reaction time from 0-1.5 seconds
- ADA Compliant Hands-Free, Germ-Free Operation
- NexGen switches are extremely thin and utilize no moving parts.
 The 4" faceplate is bordered by a clear bezel edge that illuminates upon activation



Technical Information

- Temperature Range: -13°F to 140°F (-25°C to 60°C)
- Faceplate sizes:
 4 1/2"W x 4 1/2"H (Fits Single-gang or 2-gang box)
 2 3/4"W x 4 1/2"H (Fits Single-Gange Box)
- Black acrylic finish (std.)
- Adjustable Reaction Time: 0.05-3 sec

- Adjustable Detection Range
- Form C Relay output
- Heavy Duty 1 Amp Contact
- Input Voltage: 12V to 24V AC or DC, not polarity sensitive AC

Listings and Approvals



American National Standards Institute (ANSI)




Building Hardware Manufacturers Association (BHMA) - ANSI/BHMA A156.10 & A156.19

Warranty

1 Year Limited Manufacturer's Warranty

Dimensions





Detex Corporation
302 Detex Drive
New Braunfels, Texas 78130-3045 USA
PH. (830) 629-2900
(800) 729-3839
FAX (800) 653-3839
http://www.detex.com
USA Sales:
marketing@detex.com
International Sales:

export@detex.com



Cancer & Reproductive Harm - www.detex.com/prop65