





	EAX-300	EAX-3500	EAX-411SK	EAX-4200
	Door Prop Alarm	Timed Bypass and Door Prop Alarm	AC Powered Door Prop Alarm	Door Management Alarm
				
Door Alarm	If set at 1 second. Provides alarm with auto re-arm	•	If set at 0 seconds	If set at 0 seconds
Door Prop Alarm	•	•	•	•
Part of a door monitoring system			•	•
Prop time allowed	1 second to 4 minutes	5 to 40 minutes	0 to 60 seconds	0 seconds to 90 minutes
Surface Mount	•	•		
Flush Mount		•	•	•
Battery Powered	9V Battery			
Hardwired		12 to 24 VAC	12 or 24 VAC/VDC	12 to 24 VAC/VDC @250 mA
Battery Backup	n/a	Included		
Can tie into a security system		•	•	•
Alarm type	100dB Piezo	100dB Piezo	80dB Piezo	96dB or 103dB Field Selectable
Available Weatherized	•			
Color/s available	Gray or Black	Black	Tan standard - Can have custom paint or Stainless Steel	Tan standard - Can have custom paint or Stainless Steel
Listings and Approvals	UL Listed Miscellaneous Fire Door Accessory			
Listings and Approvals	ANSI 156.29 Listed			
All mounting material included	•	For surface mount. Other kits available	•	•
Status indicator light available	•	•		•
Tamper resistant housing	•	•	n/a	n/a
Automatic alarm reset on closing	•	In prop mode if time is unexpired	•	•
Uses magnetic sensors	•	•	•	•
Optional cylinder type available	Mortise	Mortise	n/a	Rim
Includes LED indicator lights	•	•		•
Alarm signage included	•	•		
Door chime option	•			
Low battery alert	•	•	n/a	n/a
Cover lock cylinder can be ordered keyed alike	•	•		
Optional cylinder or SFIC Housing available	•	•		•
Easy to follow instructions printed on cover		•		
Warranty	3 Year	3 Year	3 Year	3 Year